



Il marchio della gestione forestale responsabile



**Rismacqua.** Carte e cartoncini multiuso dai colori tenui per l'ufficio, la casa, la scuola e il tempo libero. Ideali per tutti i sistemi di copiatura e stampa (inkjet, laser, offset...). Tutti i colori sono resistenti alla luce. Le carte sono ricavate da impasti a base di cellulose selezionate chlorine free (ECF) non provenienti da foreste vergini.

Collo di spedizione:

- Scatola contenente 5 risme dello stesso colore.

**Rismacqua.** Multipurpose, soft-coloured paper and cardboard for office, home, school uses and leisure. Suitable for all kind of photocopying and printing (inkjet, laser, offset...). All colours are light-resistant. The paper is obtained from selected chlorine free (ECF) cellulose, which does not derive from virgin forests.

Packaging:

- Carton box containing 5 reams of the same colour.

## RISMACQUA

### A4 21x29,7 cm

300 fogli/sheets  
90 g/m<sup>2</sup>

200 fogli/sheets  
140 g/m<sup>2</sup>

125 fogli/sheets  
200 g/m<sup>2</sup>

### A3 29,7x42 cm

300 fogli/sheets  
90 g/m<sup>2</sup>

200 fogli/sheets  
140 g/m<sup>2</sup>

125 fogli/sheets  
200 g/m<sup>2</sup>

- 110 avorio
- 07 giallo chiaro
- 02 camoscio
- 05 salmone
- 10 rosa
- 06 lilla
- 08 celeste
- 09 verde chiaro
- 12 ghiaccio

A66Q304	A65Q204	A67Q104	A66Q313	A65Q213	A67Q113
A662304	A652204	A672104	A662313	A652213	A672113
A66R304	A65R204	A67R104	A66R313	A65R213	A67R113
A665304	A655204	A675104	-	-	-
A66S304	A65S204	A67S104	A66S313	A65S213	A67S113
A669304	A659204	A679104	A669313	-	A679113
A66T304	A65T204	A67T104	A66T313	A65T213	A67T113
A66P304	A65P204	A67P104	A66P313	A65P213	A67P113
A66U304	A65U204	A67U104	A66U313	-	A67U113

## RISMALUCE / RISMACQUA SCHEMA TECNICA – TECHNICAL CHART

Characteristic	Standard	Unit	rismaluce / acqua 90 g.	rismaluce / acqua 140 g.	rismaluce / acqua 200 g.
Grammage / Grammaturo	ISO 536	g/m <sup>2</sup>	90±5%	140±5%	200±5%
Thickness / Spessore	ISO 534	µm	116±5%	172±5%	228±5%
Bulk / Mano	ISO 534	cm <sup>3</sup> /g	1,29	1,23	1,14
CIE dL*	ISO 2469-70	-	45-92	45-92	45-92
burst index	ISO 2758	kPa*m <sup>2</sup> /g	2,8	3,0	2,3
ash content/ceneri	ISO 1762	%	16-20	16-20	16-20
Roughness/Liscio Bendtsen FELT SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Roughness/Liscio Bendtsen WIRE SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Absolute Humidity	ISO 287	%	6.0±1.0	6.0±1.0	7.0±1.0

1. Paper type: MULTIPURPOSE PAPER / OFFICE PAPER
2. Degree of processing: UNCOATED PAPER
3. Specifications (A3 = cm 29,7x42 – A4 = cm 21x29,7)
4. Fiber type and composition: 25% LONG FIBERS; 75% SHORT FIBERS (BLEACHED CHEMICAL PULP)
5. Manufacturer name: CARTOTECNICA FAVINI S.R.L.
6. COLOURED PAPER

Data / Date: 3.08.2017

**Cartotecnica Favini S.r.l.**

Direttore Generale  
Andrea Bertone

